



### EDGE® BALE SPEARS

Farmers and other agricultural professionals can appreciate the increased productivity of a skid steer with the addition of any EDGE bale spear attachment. Whether you're moving a round or square bale, you are sure to find the bale mover that is right for you.

### OPERATIONAL BASICS

EDGE bale spears come in three options: single spear, double spear and triple spear. The single and double bale spears will move round bales from 2,200 to 3,000 lbs (997 to 1360 kg). The bolt-in tapered spears have a useable length of 42" (1067 mm). The 12" stabilizer tines are 1" in diameter.

Triple bale spears are capable of moving standard or large rectangular bales from 3,000 to 4,000 lbs (1360 to 1814 kg). Bolt-in tapered tine lengths are 26" and 42" (550 mm and 1067 mm) depending on model. An optional upright kit with 12" x 1" diameter stabilizer spikes allows two large square bales to be moved at one time.



SSB2200



SSB3000



SSRB330



SSRB340 - shown with optional uprights

### SPECIFICATIONS

Model	Weight (lbs/kg)	Tine Length (in/mm)	Cap. (lb/kg)	Bale Type
SSB-2200	129/59	(1) 42/1067 (2) 12/305	2200/998	Round
SSB-3000	146/66	42/1067	3000/1360	Round
SSRB-330	165/75	26/660	3000/1360	Square/Rectangle
SSRB-340	190/86	42/1067	4000/1814	Square/Rectangle
Bolt-On Upright Kit (optional)	32/15	42/1067	-	-

	Radial Skid Loaders							Vertical Skid Loaders			Track Loaders			Articulated Loaders			
Machine Compatibility Gehl / Mustang	3640E/ 2026	R135/ 1350R	R150/ 1500R	R165/ 1650R	R190/ 1900R	R220/ 2200R	R260/ 2600R	V270/ 2700V	V330 3300V	V400/ 4000V	RT175/ 1750RT	RT210/ 2100RT	RT250/ 2500RT	340	540	650/ 608	750/ 708
*Bale Spears	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆

\*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment